

# ACE-828C

250 W PS/2 24 V DC Input ATX Type

## Features

250 W PS/2 24 V DC Input ATX Type



## Specifications

| General               |  |
|-----------------------|--|
| Efficiency            | 65%  |
| MTBF                  | 120,000  |
| Operating temperature | -20°C ~ 70°C   |
| Output Connector      | 1 x P8+P9, 1 x Extra +5V (P10), 4 x HDD/CDROM, 2 x FDD |
| Storage temperature   | -40°C ~ 75°C   |
| Watt                  | 250W   |
| Input                 |  |
| Voltage               | 18 ~ 32 VDC  |
| Input Current         | 20 A (RMS)@24VDC                                       |
| Inrush Current        | 20 A (RMS)@24VDC                                       |
| Output                |  |
| Voltage               | +3.3V/8A,+5V/25A,+12V/7A,-5V/0.5A,-12V/1A,+5Vsb/0.72A  |
| Ripper&Noise          | +5 V, +3.3 V output are less than 50mV                 |
|                       | +12 V, -5 V, -12 V, +5 Vsb output are less than 100mV  |

## Ordering Information

|             |  |
|-------------|--|
| ACE-828C-RS | +24V DC input industrial ATX power supply;;;CCL;RoHS |
|-------------|--|