

DM2-121

12.1" 最新一代工业显示器



Features

- » 前置 OSD，便于设置调整
- » 前置扬声器，即使在面板安装中也能确保清晰的声音传输
- » 支持戴手套操作和防水保护
- » 内置摄像头，适用于 AI 面部识别
- » USB 3.2 Gen1 Type-A 支持 10W
- » 符合 IP65 标准的前面板与铝制框架
- » 防眩光和抗紫外线
- » 高亮度 (HL only)

Specifications

Display	
LCD Size	12.1" (4:3)
Brightness(cd/m2)	500 (1000 for HL)
Max Resolution	1024 x 768
Contrast Ratio	1000:1
Backlight MTBF(hrs)	50000
I/O Interface	
I/O Ports	1 x VGA (DB-15)
	1 x HDMI
	1 x DisplayPort1.1
	1 x USB 3.2 Gen1 Type-B
	4 x USB 3.2 Gen1 Type-A (5V2A) (Lite版不带)
	1 x Line out
	1 x 9V-36V DC jack
	1 x 3-pin terminal block
Power	
Power adapter	12V 直流
Environment	
工作温度	-20°C ~ 60°C
相对湿度	10% to 95%@40°C (无冷凝)
存储温度	-20°C ~ 70°C
IP Level	前面板 IP 65
Physical Characteristics	
机身颜色	黑色 + 银色
尺寸 (LxWxH) (mm)	279.86 x 237.50 x 49.30
Cutout Dimensions	270.50 x 214.10
LCD	
LCD 色彩	16.2M
可视角度 (H-V)	178°/178°
Touch	
触摸屏	10点电容式触控屏(防紫外线, 防眩光表面)
触控IC	Capacitive:litek

Ordering Information	
DM2-121E-R10	12.1" 500 cd/m ² 1024 x 768 monitor, VGA, HDMI, DisplayPort, with USB 3.0 HUB, USB PC touch screen, 9 ~36V DC input, Speaker, Camera, R10
DM2-121EL-R10	12.1" 500 cd/m ² 1024 x 768 monitor, VGA, HDMI, DisplayPort, USB PC touch screen, 9 ~36V DC input, Lite, R10
DM2-121EL-HL-R10	12.1" 1000 cd/m ² 1024 x 768 monitor, VGA, HDMI, DisplayPort, USB PC touch screen, 9 ~36V DC input, Lite, R10
DM2-121E-HL-R10	12.1" 1000 cd/m ² 1024 x 768 monitor, VGA, HDMI, DisplayPort, with USB 3.0 HUB, USB PC touch screen, 9 ~36V DC input, Speaker, Camera, R10

Packing List

1 x DM2-121	1 x USB-touch 线
1 x 3-pin 凤凰端子	4 x VESA 螺丝
8 x Panel Mount 支架	