

IOVU-752S

7" TFT WVGA LCD with resistive touchscreen



Features

- » 7" TFT WVGA LCD with resistive touchscreen
- » Samsung S3C6410 ARM11 677MHz CPU
- » Powered by Windows® CE 6.0
- » Built-in Ethernet LAN
- » Built-in RS-232/422/485 Port
- » Supports Power over Ethernet (PoE)
- » Multimedia support for MPEG-4/H.263/H.264
- » Support .Net Frame Work V3.5

Specifications

Environment	
Operating Temperature	-10°C~ 60°C
LCD	
Brightness (cd/m2)	400
Resolution	VGA
Size	5.7"
Viewing Angle (H-V)	140° / 100°
Physical Characteristics	
Dimensions (LxWxH) (mm)	180 x 135 x 46
Net Weight	0.7 Kg
Power	
Power adapter	12~36V DC input
Power consumption	Max. 14W
System	
CPU	XScale® PXA310 624 MHz
Memory Ext.	256 MB DDR2
On-board Memory	128 MB
Touch	
Touch Screen	Resistive Type
I/O Interface	
I/O Interface	2 x Speaker(1.5W)
	2 x USB 1.1
	1 x Power In(terminal block DC input)
	2 x LAN(10/100Mbps)
	1 x SD Slot
	1 x Reset Button
	1 x RS-422/485
	1 x WIFI(802.11a/b/g/n)

Ordering Information

IOVU-752S-CE6/-R10

RISC PANEL PC 8.4"以下,7" LCD,SAMSUNG S3C6410X66-YB40 667MHz WITH POE FUNCTION,WIN CE6.0,RoHS