

EBC-2100

Embedded C EBC-2100 hassis for EPIC NANO Series



Features

- » Fanless system with AMD LX-800
- » Complete I/O interfaces, including LAN, COM, four USB
- » Single 12V DC power input, AT mode only
- » DDR support up to 1GB

Specifications

| | |
|-----------------------------|--------------------------------------|
| Form factor | |
| SBC Form Factor | Refer to SBC |
| | SBC Size (mm): EPIC (165 x 115) |
| I/O Interface | |
| I/O Ports | 1 x PS/2 |
| | 4 x USB2.0 |
| | 1+2 RS-232 |
| | 1 X LPT (optional) |
| | 1 x Realtek 8100C |
| | 3 x Audio jack (optional) |
| Expansion Slots | |
| Expansion Slots | 1 x PCI-104 |
| System | |
| Cooling method / System Fan | 40 x 40 x 10 (optional) |
| Drive Bays | 1 x 2.5" SATA HDD drive bay |
| | 1 x CF Card/CFast |
| Physical Characteristics | |
| Construction | Aluminum alloy with heavy duty metal |
| Color | |
| Color | Cool gray |
| Dimensions | |
| Dimensions | 262 x 134 x 56 |
| Weight | |
| Weight | 1 kg/3 kg |
| Environment | |
| Operating Temperature | 0°C ~ 50°C |

Ordering Information

| | |
|--------------|--|
| EBC-2100-R41 | Embedded chassis for NANO-8522/LX,compatible with 2.5" SATA hard drive,60W power adapter with ERP and PSE certificates,sliver,RoHS |
|--------------|--|

Packing List

| | |
|---------------------------|--------------------|
| 1 x 12V 60W power adapter | 1 x Power cord |
| 1 x Screw set | 1 x Wall mount kit |
| 1 x QIG | |