

ACE-A140B

400 W PS/2 ATX Power Supply with ErP



Features

400 W PS/2 ATX Power Supply with ErP

Specifications

| Input | |
|--------------------------|---|
| Voltage | 90~264 VAC Full Range |
| Frequency | 47 Hz ~ 63 Hz |
| Input Current | 5A (RMS)@115VAC, 2.5A (RMS)@230VAC |
| Inrush Current | 80A max. for 115VAC, 160A max. for 230VAC |
| Output | |
| Voltage | +3.3V/21A,+5V/16A,+12V1/17A,+12V2/17A,-12V/0.5A,+5Vsb/3A,-5V/0.1A |
| Over Voltage Protection | +3.3V: 3.76V-4.3V |
| | +5V: 5.74V-7.0V |
| | +12V1 and +12V2: 13.4V-15.6V |
| Short Circuit Protection | +3.3V, +5V, +12V or -12V shutdown and latch off |
| General | |
| Watt | 400 |
| Efficiency | 87% |
| MTBF | 100000 |
| Operating temperature | 0°C ~ 50°C |
| Storage temperature | -20°C ~ 80°C |
| Dimensions | 140 x 150 x 86 |
| Output Connector | 1 x 20+4-PIN ATX, |
| | 2 x 4-pin 12V CPU, |
| | 8 x HDD/CDROM, |
| | 1 x Graphics card power, |
| | 2 x FDD, |
| | 2 x SATA |

Ordering Information

| | |
|-----------------|--|
| ACE-A140B-S-R11 | 400W PS/2 ATX Power Supply with ERP & on/off switch,meets 80 plus(Gold);RoHS |
| ACE-A140B-R11 | 400W PS/2 ATX Power Supply with ERP,meets 80 plus(Gold),RoHS |